



AT-MONO 3/SP

Moving Coil Cartridge

The Audio-Technica AT-MONO 3/SP cartridge is special – redesigning not just the needle, but the whole cartridge specially for “shellac” or phonograph records. A high output moving coil cartridge of excellent production quality and wound with PCOCC coil for signal purity, it is designed to deliver excellent fidelity and superb clarity when playing 78 RPM mono records. With its high output of 1.2 mV, it can be used without additional pre-amplification or a MC transformer.

Proven in use for many years in Japan, the Audio-Technica AT-MONO 3/SP cartridge is now available in Europe and helps to bring back the pure joy of discovery and listening pleasure for 78rpm record playing.



AT-MONO 3/SP

PCOCC

PCOCC = Pure Copper by Ohno Continuous Casting process

RRP ex VAT 189,00 €

RRP inc. VAT £199.00

Ean code: TBA

Specifications*:

Type:	Moving Coil, Mono 78 RPM Mono cartridge
Frequency response:	45 - 7,000 Hz
Output voltage:	1.2 mV (1kHz and 5 cm/sec)
Tracking force:	3.0 - 7.0 g (5.0 g standard)
Recommended load:	40 ohms - 47K ohms (determine best value by listening)
Channel separation:	Not applicable
Channel balance:	Not applicable
Cantilever:	Aluminum alloy
Stylus:	Highly polished special conical 2.5 mil diamond
Dynamic compliance:	7.0 x 10-6 cm/dyne
Static compliance:	20.0 x 10-6 cm/dyne
External size:	H16.0 x W16.6 x L26.5 mm
Weight:	6.8 g
Accessories included:	Screwdriver, 4 screws, 2 washers and 2 nuts, spacer/weight, stylus brush

* Specifications are subject to change without notice.

 **audio-technica**
always listening

Audio-Technica Limited, Old Lane, Leeds LS11 8AG England
 Audio-Technica SAS, 28 rue Godefroy-Cavaignac, 75011 Paris, France
 Audio-Technica Niederlassung Deutschland, Stiftstrasse 18, D-65183 Wiesbaden, Germany
 ©2010 Audio-Technica, www.audio-technica.com